



**HEADS**  
CAULKING BY OTHERS

**JAMBS**

**SILLS**

**EXPANSION ANCHOR**  
(TYP 4 SIDES)

**WOOD SCREW**  
(TYP 4 SIDES)

**SHEET METAL OR SELF TAPPING SCREW**  
(TYP 4 SIDES)

**SHEET METAL OR SELF TAPPING SCREW**  
(TYP 4 SIDES)

**TYPICAL MASONRY WALL OPENING** 1

**TYPICAL WOOD FRAME WALL OPENING** 2

**TYPICAL DEEP CURTAIN WALL OPENING** 3

**TYPICAL NARROW CURTAIN WALL OPENING** 4

**INSTALLATION NOTES:**

1. WIDTH & HEIGHT DIMENSIONS ARE OPENING SIZES. LOUVERS ARE MADE UNDERSIZE. TYPICAL 1/8" AROUND PERIMETER OF LOUVER FRAME. MFM CAN SUPPLY LOUVERS WITH LARGER UNDERSIZING UPON REQUEST.
2. ALL STRUCTURAL SUPPORTS, CLIPS ANGLES, MOUNTING FASTENERS, CAULKING, SHIMS, MASONRY ANCHORS, ETC. ARE BY OTHERS AND ARE NOT SUPPLIED OR INSTALLED BY MFM AS STANDARD.
3. THESE ARE GENERAL MOUNTING ARRANGEMENTS FOR LOUVER WALL OPENINGS. VIEWS SHOWN SHOULD COVER MOST MOUNTING SITUATIONS ENCOUNTERED. LARGE MULTIPLE WIDE AND/OR HIGH LOUVER PANEL ASSEMBLIES REQUIRE STRUCTURAL SUPPORT ON INTERIOR OF LOUVER PANELS (NOT SUPPLIED BY MFM)
4. BECAUSE LOCAL BUILDING CODES AND INSTALLATION STANDARDS VARY, MFM RECOMMENDS THEY BE USED WHEN AND WHERE REQUIRED.



**"The ART of Noise Control"**  
 For your local ArtUSA Representative  
 Call: 1-888-454-6973  
 Internet: [www.artusaindustries.us](http://www.artusaindustries.us)